

PLASTIC ODB BOXES FOBOS SERIES

12/24 PORT WALLMOUNT TYPE



OVERVIEW

TTAF's outdoor fiber wall mount distribution boxes are designed to offer the most flexible solution for all FTTx networks. Suited to pole or wall mounting the all in one flexible distribution box is the ideal fit for today's FTTx networks. The all passive optical network components are housed in a single enclosure that offers the highest level of cable management.

Features

APPLICATIONS

- » Optical networks
- » Enterprise
- » FTTx

CONNECTIONS

- » Termination count 12 SC Simlex or 24 LC Duplex
- » Termination types are SC, LC per BOX.
- » Recommended patchable thickness 2-3mm



BENEFITS

- » Breakout cable inlet
- » Sx/Dx cable inlet- Waterproof silicone gaskets
- » Cable fixing
- » Plate fixing
- » Adapter holder
- » Safety lock
- » Ground pin
- » Splice cassette lock

SPECIFICATIONS

| | |
|-----------------------|------------------------------------|
| Dimensions | 210mm (w) X 150mm (H) X 50mm (D) |
| Weight | Approx. 550 gr |
| Mounting | Wall Mounted |
| Material | ABS 757 |
| Operating Temperature | -40 / +60 |
| Operating Humidity | 0 to 90 % |
| IP rating | IP67 |
| Vibration | 10~55~10HZ / 10 min for 2 hours |

- » Minimum bending radius is 30mm throughout box laser radiation protection. Adapter location prevents exposure.
- » ODB BOX can be opened up to 270°