

## AUDIO / VIDEO

### USB / USB - V2.0

#### ADAPTOR



### USB / USB - V3.0

#### ADAPTOR



#### MATERIAL

Housing : White ABS High-Impact UL94V-0 Thermoplastic.  
 Shell : Copper Alloy, Tin-Lead Plated Over Copper.  
 Plastic : PBT High-Impact UL94V-0 Thermoplastic, Glass Filled 130°C.  
 Contact : Copper Alloy 3U" Gold-Plated RoHS Compliant.

#### MATERIAL

Housing : White ABS High-Impact UL94V-0 Thermoplastic.  
 Shell : Copper Alloy, Tin-Lead Plated Over Copper.  
 Plastic : PBT High-Impact UL94V-0 Thermoplastic, Glass Filled 130°C.  
 Contact : Copper Alloy 3U" Gold-Plated RoHS Compliant.

#### PHYSICAL CHARACTERISTICS

Durability : EIA 364-09,1500 Cycles.  
 Temperature : -55°C+85°C.  
 Humidity : 10%-90%RH.

#### PHYSICAL CHARACTERISTICS

Durability : EIA 364-09,1500 Cycles.  
 Temperature : -55°C+85°C.  
 Humidity : 10%-90%RH.

#### ELECTRICAL

Voltage : 30 VAC  
 Current : 1.5 AMPS MIN,PER CONTACT AT 30°C T-RISE  
 Insulation Resistance : 10 Mohm MINIMUM  
 Dielectric With Standing Voltage : 300 V AC.  
 Contact Resistance : 2 ohm MAX INITIAL.

#### ELECTRICAL

Voltage : 30 VAC  
 Current : 1.5 AMPS MIN,PER CONTACT AT 30°C T-RISE  
 Insulation Resistance : 10 Mohm MINIMUM  
 Dielectric With Standing Voltage : 300 V AC.  
 Contact Resistance : 2 ohm MAX INITIAL.



2 PORT HDMI&USB 2.0  
FACE PLATE



2 PORT HDMI&USB 3.0  
FACE PLATE

Art No	Product Description	Art No	Product Description
FO-AD-USB2	22,5 X 45 USB 2.0 Adaptor	FO-AD-USB3	22,5 X 45 USB 3.0 Adaptor

